

armastone

Naturally Timeless

ERRIGAL SPLIT FACE (ANTIQUED) SAND STONE



Product Information

- Type: Sand Stone
- Finish: Split Face
- Colour: Beige/Mint
- Application: Interior and Exterior Vertical

Technical Information

- Flat panel: 15 x 61cm
- Thickness: 10-18mm
- Weight: 3.1-3.6kg
- Panels: 6 pcs/box; 288 pcs/crate

Packaging

Flexural Strength/Modulus of Rapture N/mm²

S.NO.	DRY		WET		ASTM STANDARDS
	PARALLEL TO RIFT	PERPENDICULAR TO RIFT	PARELLEL TO RIFT	PREPENDICULAR TO RIFT	
1	42	39	35	37	C-99
2	41	41	34	39	
3	43	40	33	38	
AVE. VALUE	42	40	34	39	

Compressive Strength N/mm²

S.NO.	DRY		WET		ASTM STANDARDS
	PARALLEL TO RIFT	PERPENDICULAR TO RIFT	PARELLEL TO RIFT	PREPENDICULAR TO RIFT	
1	157	184	133	154	C-170
2	156	185	134	153	
3	155	186	135	152	
AVE. VALUE	156	185	134	153	

Abrasion (Resistance to Wear)

CHARACTERISTICS	VALUE	ASTM STANDARDS
Average Wear .mm	0.9	IS 1237 GUIDELINES
Maximum Wear On Individual Specimen.mm	1.0	

Water Absorption

TECHNICAL INFORMATION	VALUE	ASTM STANDARDS
Water absorption % by weight	1.0	C-97
Density (bulk specific gravity)	2.40	C-97

Resistance to Frost

FREEZE THAW TEST	TEST STANDARD	OBSERVATION
-18°C TO +32°C FOR 8 HOURS. 5 CYCLES	ASTM D-5312-04	SPECIMEN NOT SHOWING SPLITTING OR DISINTIGATION